

(19) World Intellectual Property
Organization
International Bureau



MAY 2005



(43) International Publication Date
17 June 2004 (17.06.2004)

PCT

(10) International Publication Number
WO 2004/050537 A2

(51) International Patent Classification⁷: **B67D 1/04**

(21) International Application Number:
PCT/TB2003/005399

(22) International Filing Date:
25 November 2003 (25.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0227930.5 29 November 2002 (29.11.2002) GB
0227931.3 29 November 2002 (29.11.2002) GB

(71) Applicant (for all designated States except US): **INTER-BREW S.A.** [BE/BE]; Vaarstraat 94, B- 3000 Leuven (BE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **WAUTERS, Albert** [BE/BE]; Admiraalhof 24, B- 9070 Destelbergen


(BE). **ANDERSON, Ian** [GB/GB]; 19 Silver Street, Burwell, Cambridge CB5 0EF (GB). **DUFFY, Edward, P.** [GB/GB]; 61 Green Drift, Royston, Herts SG8 5BX (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: **BEER DISPENSING SYSTEM WITH GAS PRESSURE RESERVOIR**



(57) Abstract: A home beer dispensing apparatus has a keg having a self-contained bag filled with a beer and a pressure system. The pressure system creates a pressurized air space between the keg inner walls and the bag to assist in the dispensing of the beer. The pressure system has a keg one-way air valve mounted to a top wall of the keg to permit entry of pressurized air into the keg. The pressure system has a pressure reservoir mounted in the dispensing apparatus outside the keg and in fluid flow communication with the keg one-way valve. The reservoir stores a charge of pressurized air and supplies at least a portion of this charge to the keg through the keg air valve when the dispensing apparatus is operated to dispense the beer. The reservoir provides a reserved charge of pressurized gas that is on hand to reduce dampening pressure fluctuations during beer dispensing which can result in beer frothing, especially during the early stages of beer dispensing when the air head

space in the keg is small. Further, the apparatus may also have a pressure sensing system adapted to measure time rate of pressure change in the keg. The apparatus has a signaling device responsive to the time rate of pressure change in the keg to produce a signal related to volume of beer remaining in the bag. Preferably, the signal is displayed visually on the dispensing apparatus.

WO 2004/050537 A2



Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.